

MK1380 数控大型外圆磨床

CNC LARGE CYLINDRICAL GRINDER



机床用途与性能特征

- MK1380数控外圆磨床主要适用于重型机械、塑料机械及造纸、橡胶、印染等行业中，磨削各种金属、非金属压辊及其它工件外圆。
- 采用德国西门子数控系统，实行人机对话方式，设定磨削程序，内置PLC，CRT显示，两轴联动，分别驱动砂轮架和工作台的运动。
- 机床的砂轮架主轴采用动静压轴承，配置温度控制油箱，稳定性好，且砂轮具有恒线速功能。
- 机床具有砂轮自动切入或周期进给，工作台自动跳档，工件尺寸的自动测量，砂轮自动两轴联动修整砂轮和修整后的自动补偿。在工件一次装夹后，即可完成一个或多个轴颈的磨削加工，是一种高效、高精度的机床。
- 工作台和砂轮架驱动电机为大惯量交流伺服电机，配置全封闭防护及操纵台，提高操作安全。

Main Applications and Structural Features

- MK1380 series mainly used in the fields of nearly machinery, plastic machinery, paper making, rubber, and dye printing grind various of metallic, nonmetallic compression roller and other workpieces.
- It adopts German SIEMENS CNC system, PLC, CRT display built in, two axis linkage, drive the movement of grinding carriage and worktable separately.
- Spindle of grinding carriage adopts dynamic static pressure bearing, with temperature-control oil box, good stability, and wheel owns CLV function.
- Head stock is adjusted speed by AC motor, whose speed can be adjustable steplessly to meet different grinding of workpieces.
- The drive motor of worktable and grinding carriage is AC Servo motor, suitable for machining large spareparts.
- Full-closed protecting cover-B provided, which makes environment much better.

技术规格参数 Specifications and Technical Parameters

磨削直径Diameter to be ground	Φ100 ~ Φ800mm
顶尖距Distance between centers	3000、4000、5000mm
中心高Height of center	410mm
最大工件重量Max. weight of workpiece	5000Kg
砂轮尺寸Max. dimension of grinding wheel	Φ900 × 75 × Φ305mm
砂轮速度Speed of grinding wheel	35m/s ~ 45m/s
砂轮架速度Wheel frame rate	0.1 ~ 500mm/min
X、Y轴分辨率X, Y axis resolution	0.001 or 0.0001mm
工作台速度Hydraulic traverse speed	1 ~ 10000mm/min
主电机功率Main electrical machinery power	22KW
顶尖号Apex number	公制100

机床工作精度 Working Accuracy

(标准试件CriterionTyr the Piece Φ200 × 800 45# Chilled steel)

圆度Roundness	≤2 μm
纵截面上直径一致性Uniformity of dia. in longitudinal section	≤3 μm
粗糙度Roughness	0.32 μm

机床主要附件 Main Accessories

全套电器设备	Complete set of electric equipment
冷却设备	Complete set of coolant equipment
砂轮修整器	Cylindrical wheel dresser
开式中心架	Open-type steady-rest
莫式顶尖	Mo type top
砂轮法兰盘	Wheel adaptors flange
砂轮平衡轴	Wheel balancing mandrel
机床垫铁	Iron cusion

特殊定货附件 Extra Accessories

砂轮平衡架	Wheel balancing stand	1套 set
磁辊纸带过滤的冷却水箱	Cooling water box	1套 set
镶块顶尖	Carbide-tipped center	1件 piece
磨顶尖装置	Center grinding unit	1套 set
开式中心架	Open-type steady rest	1/2/3套 set
马波斯测量仪(端面)	Precision cylindricat meter	1套 set
SBS或马波斯自动平衡仪	Automatic balance recording meter	1套 set

由于产品不断创新，本资料仅供参考，如有修改恕不通知，本公司保留最终解释权。
As products are improving gradually, the above information is only for reference, if any modification without notification, we company reserves the final explanation rights.